

## SERIES 130-H - 130 KN

### MAIN CHARACTERISTICS PP130-H - HPI130-H - AP130-H

COMPRESSION SECTION	max. 400 mm <sup>2</sup>
MAXIMUM STROKE	30 mm

COMPRESSION FORCE	130 kN
OPERATING PRESSURE	700 bar (70 MPa)

HEAD OPENING: 35 mm



### PP130-H – Hydraulic Crimping Head

The unit must be operated through 700 bar hydraulic pump to reach compression force of 130 kN. (pages 89 - 94)

#### Technical Characteristics:

- Sturdy and compact structure
- Openable head to make it easy to position and insert the crimping dies
- Quick make snap lock connection and non detachable dust cap
- Adapters and punch for deep indent compression

Head opening: ..... 35 mm  
 Tool dimensions: ..... 78 x 263 x 70 mm  
 Tool weight: ..... 3,4 kg

Description	Order No.	Dimensions	Weight
Set crimping head	PP130-H	410 x 360 x 135 mm	5,1 kg

#### Set Equipment:

- Hydraulic crimping head
- Plastic case for crimping head and 14 crimping dies



### HPI130-H – Hand Operated Hydraulic Crimping Tool

#### Technical Characteristics:

- Sturdy and compact structure
- Crimping H-head ; rotates 270°
- Quick feed with double hydraulic cylinder
- Single hand use by innerside handle
- Automatic pressure safety valve
- Manual return in any position
- Adapters and punch for deep indent compression

Tool dimensions: ..... 174 x 569 x 78 mm  
 Tool weight: ..... 5,8 kg

Description	Order No.	Dimensions	Weight
Set crimping tool	HPI130-H	700 x 260 x 105 mm	7,6 kg

#### Set Equipment:

- Test report
- Manual crimping tool
- Plastic case for crimping tool and 11 crimping dies