



Data Sheet 1223755

Product: 45/6 dobbel 2 LØP VB
El-number: 1223755
Mat.no: EKO05231
EAN: 7020160523112
Packing: 25
Color:





Product description:

Double flush wall-box with 2 x 16 mm Ø conduit entries, locking springs and sealing plugs with plastic lid included. Also included: dividing piece for "low" and "high" voltage sections. 4 height adjusting screws are mounted in each corner of the long side of the box. The connecting pieces and tubeconnector L 601 can be fixed at either end or on the long side. Two or more boxes can be interconnected by use of connecting pieces: L 595 (cc 71 mm: under one combination-plate) and L 596 (cc 84 mm: where two combination plates meet). ELKO tripple outlets might be mounted in ELKO double boxes. The box is supplied in two depths: 45 mm and 60 mm. Extra 6 mm high extension ring for the boxes is available. The double box is very suitable for telecommunication - and datainstallations.

Technical specifications:

45 mm depth.
Standard CEE publ. 7, XIII.
Halogenfree.
Maximum temperature during casting prosess: 90°C
Minimum installation temperature: -25°C
Cuttersize: 73mm

Size



Wiring diagram

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporvind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01