

### DESCRIPTION:

A corrosion protection, pressure sensitive vinyl tape giving complete environmental, mechanical and electrical protection for all types of pipewrapping applications. UV, bacteria and fungus resistant, Plywrap 11 pipewrap tape can be used for both overhead and direct burial applications.

### TECHNICAL CHARACTERISTICS

PROPERTY	VALUE	UNIT	TEST METHOD
Color	Black	- - -	- - -
Thickness	0.010	inch	ASTM D 1000
	0,25	mm	ASTM D 1000
Tensile Strength	27	lb/in	ASTM D 1000
	48	N/cm	ASTM D 1000
Elongation	250	%	ASTM D 1000
Adhesion to Steel	22	oz/in	ASTM D 1000
	2,4	N/cm	ASTM D 1000
Adhesion to Backing	18	oz/in	ASTM D 1000
	2,0	N/cm	ASTM D 1000
Dielectric Strength	1000	V/mil	ASTM D 1000
	40	kV/mm	ASTM D 1000
Dielectric Constant	3.2	- - -	ASTM D 150
Power Factor	0.07	- - -	ASTM D 150
Insulation Resistance	1x10 <sup>6</sup>	MΩ	ASTM D 1000

Information provided is for reference only. Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use.

Revised March 2013



### FEATURES:

- Highly resistant to sun, water, oil, acids, alkalies and corrosive chemicals
- Lead-free
- Bacteria and fungus resistant
- Abrasion resistant
- Meets Federal Spec. L-T-1512A

### RECOMMENDED USES:

Protect pipes, pipe joints, conduit and couplings in overhead or direct burial applications. Protects from all types of corrosion.

### STANDARD SIZES:

- 1 in x 100 ft  
25 mm x 30 m
- 2 in x 100 ft  
50 mm x 30 m

Other sizes are available upon request

**LIMITED WARRANTY:** Plymouth warrants that its Product will substantially conform to that products written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment, (Unless provided otherwise in product's data sheet). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (rev. 1/95)