

## 20 PLYSIL® Silicone Rubber Tape

A 20 mil (0,51mm) triangular cross-section, self-amalgamating, silicone rubber tape used for jacketing high voltage terminations on solid dielectric cable through 69kV. 20 Pylsil is track and erosion resistant and can be used as primary insulation for high temperature (180°C) applications. ASTM-D-2148, MIL-I-46852A.

## 77 PLYGLAS® Pressure Sensitive Glass Cloth Tape

A 7 mil (0,18mm) woven glass fabric tape with a thermosetting rubber based, pressure sensitive adhesive used for insulating and protecting high temperature (130°C) connections, such as motor leads and transformer windings. 77 Plyglas has high tensile strength for splice reinforcement and provides excellent tear and abrasion resistance. Use 77 Plyglas to hold down 53 Plyarc arc- and fire-proofing tape. Comm. Spec. 7611, ASTM-D-2754, MIL-I-15126F/GFT.

## 53 PLYARC® Arc and Fireproofing Tape

A 30 mil (0,76mm) elastomeric tape that provides excellent flame and arc protection for all types of cables. When exposed to flame, 53 Plyarc will generate a thermally insulating residue for cable protection. Use on cable conduit where added fire protection is required. Excellent flexibility and conformability for easy application. Available in grey.

## SPECIAL PURPOSE PRODUCTS



### 20 PLYSIL® Silicone Rubber Tape

Cat.	Dimensions	Packaging	Weight
3455	1" x .020" x 30' 25mm x 0,51mm x 9,1m	50/case C	18 lbs 8 kg

### 77 PLYGLAS® Pressure Sensitive Glass Cloth Tape

Cat.	Dimensions	Packaging	Weight
3451	1/2" x .007" x 66' 13mm x 0,18mm x 20m	50/case B	9 lbs 4 kg
3456	3/4" x .007" x 66' 19mm x 0,18mm x 20m	50/case B	12 lbs 5 kg
3459	1" x .007" x 108' 25mm x 0,18mm x 33m	20/case B	37 lbs 17 kg

### 53 PLYARC® Arc and Fireproofing Tape

Cat.	Color	Dimensions	Packaging	Weight
3817	Grey	1 1/2" x .030" x 20' 38mm x 0,76mm x 6,1m	20/case C	13 lbs 6 kg
3819	Grey	3" x .030" x 20' 76mm x 0,76mm x 6,1m	10/case C	13 lbs 6 kg
2630	Grey	14" x .030" x 14" 357mm x 0,76mm x 357mm	300/case B	110 lbs 50 kg
3816	Grey	1" x .030" x 20' 25,4mm x 0,76mm x 6,1m	30/case C	13 lbs 6 kg